



AIR-HYDRAULIC PUMP SHDL1000-2500





ADVANTAGES

The FASTEC SHDL - Series is a high-capacity, compact air-hydraulic high-pressure unit, specially designed for industrial use

- Low air pressure for extreme working pressures
 1 bar air pressure = 440 bar hydraulic pressure
- Rugged, compact and durable design
- Manufactured in high-quality materials
- Small dimensions and low weight
- Immediately ready for use, fully assembled and oil filled
- All components sealed leakproof, no pressure loss even at 2.500 bar
- Hardened, replaceable valve seats
- Pressure release valve with internal tank return line
- Permanently installed in steel housing
- Low-maintenance operation
- Distributor block for up to four connections

TECHNICAL DATA:

(further versions on request)

Max. hydraulic pressure:	2.500 bar
Safety valve on the	Factory set approx. to max. hydraulic pressure
air pressure side:	2.500 bar / 1.600 bar / 1.000 bar
Pressure intensifier:	Pressure ratio from 1 bar air pressure to 440 bar hydraulic pressure
Maintenance unit:	Adjustable pressure reducer and oil injector for working with oiled compressed air
Pressure connection:	According to type key
Pressure gauge:	Ø 100, Class 1,0, filled with glycerine, 2.500 bar / 1.600 bar / 1.000 bar
Air cut off valve:	Hand and /or foot operated
Tank:	Aluminium tank with 6 litre useable volume and externally visible oil level gauge
Hydraulic oil:	HLP ISO VG 15
Set up:	Maintenance-friendly arrangement of the components, steel tube frame
Weight (filled with oil):	approx. 33 kg
Dimensions:	L640 mm x W352 mm x H340 mm
Packaging:	Pallet

FASTEC AG

INDUSTRIEZONE FON +41 41 875 78 30 SCHÄCHENWALD FAX +41 41 875 78 31 CH-6460 ALTDORF INFO@FASTEC.CH SWITZERLAND WWW.FASTEC.CH