


AIR-HYDRAULIC PUMP SHDL4000



ADVANTAGES

The FASTEC SHDL - Series is a high-capacity, compact air-hydraulic high-pressure unit, specially designed for industrial use

- Low air pressure for extreme working pressures
1 bar air pressure = 740 bar hydraulic pressure
- Rugged, compact and durable design
- Manufactured in high-quality materials
- Small dimensions and low weight
- Immediately ready for use, fully assembled and oil filled
- All components sealed leakproof, no pressure loss even at 4.000 bar
- Hardened, replaceable valve seats
- Pressure release valve with internal tank return line
- Permanently installed in mobile housing
- Low-maintenance operation
- Distributor block for up to four connections

TECHNICAL DATA:

(further versions on request)

Max. hydraulic pressure:	4.000 bar
Safety valve on the air pressure side:	Factory set approx. to max. hydraulic pressure 4.000 bar / 3.000 bar / 2.500 bar / 1.600 bar
Pressure intensifier:	Pressure ratio from 1 bar air pressure to 740 bar hydraulic pressure
Maintenance unit:	Adjustable pressure reducer and oil injector for working with oiled compressed air
Pressure connection:	According to type key
Pressure gauge:	Ø 100, Class 1,0, filled with glycerine, 4.000 bar / 3.000 bar / 2.500 bar / 1.600 bar
Air cut off valve:	Hand and /or foot operated
Tank:	Aluminium tank with 6 litre useable volume and externally visible oil level gauge
Hydraulic oil:	HLP ISO VG 15
Set up:	Maintenance-friendly arrangement of the components, steel tube frame
Weight (filled with oil):	approx. 34 kg
Dimensions:	L660 mm x W400 mm x H596 mm
Packaging:	Pallet

FASTEC AG
 INDUSTRIEZONE SCHÄCHENWALD
 CH-6460 ALTDORF SWITZERLAND
 FON +41 41 875 78 30
 FAX +41 41 875 78 31
 INFO@FASTEC.CH
 WWW.FASTEC.CH